

Idesco reader housings

Basic

Dimensions (hwxwdx)	110 x 43 x 24 mm
Material	Plastic
IK rating	IK-10
Protection class	IP67, pigtail cable, IP54, with connector
Inflammatory class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature	- 40 °C - +55 °C
Storage temperature	- 40 °C - +55 °C



Slim

Dimensions (hwxwdx)	141 x 43 x 19 mm
Material	Plastic
IK rating	IK-09
Protection class	IP67, pigtail cable, IP54, with connector
Inflammatory class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature	- 40 °C - +55 °C - 10 °C - +50 °C (EPC Slim)
Storage temperature	- 40 °C - +55 °C - 40 °C - +85 °C (EPC Slim)



Slim Pin

Dimensions (hwxwdx)	141 x 43 x 19 mm
Material	Plastic
IK rating	IK-09
Protection class	IP67, pigtail cable, IP54, with connector
Inflammatory class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature	-40 °C to +55 °C
Storage temperature	- 40 °C - +55 °C



VS

Dimensions	VS; W: 44,96 mm x H: 148,3 mm. Thickness: 25,3 mm (with cable), 25,3 mm + 10 mm (with connector)
Material	Plastic
IK rating	IK-09
Protection class	IP67, pigtail cable, IP54, with connector
Inflammatory class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature	- 30 °C - +55 °C
Storage temperature	- 30 °C - +55 °C



VM

Dimensions	W: 84,48 mm x H:126,25 mm. Thickness: 28 mm (with cable), 28 mm + 8,5 mm (with connector)
Material	Plastic
IK rating	IK-09
Protection class	IP67, pigtail cable, IP54, with connector
Inflammatory class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature	- 30 °C - +55 °C
Storage temperature	- 30 °C - +55 °C



VS Pin

Dimensions	VS; W: 44,96 mm x H: 148,3 mm. Thickness: 25,3 mm (with cable), 25,3 mm + 10 mm (with connector)
Material	Plastic
IK rating	IK-09
Protection class	IP67, pigtail cable, IP54, with connector
Inflammatory class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature	- 30 °C - +55 °C
Storage temperature	- 30 °C - +55 °C



VM Pin

Dimensions	W: 84,48 mm x H:126,25 mm. Thickness: 28 mm (with cable), 28 mm + 8,5 mm (with connector)
Material	Plastic
IK rating	IK-09
Protection class	IP67, pigtail cable, IP54, with connector
Inflammatory class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature	- 30 °C - +55 °C
Storage temperature	- 30 °C - +55 °C



Quattro N

Dimensions (hwxwdx)	85 x 85 x 24 mm
Material	Plastic
IK rating	IK-09
Protection class	IP67, pigtail cable, IP54, with connector
Inflammatory class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature	- 40 °C - +55 °C
Storage temperature	- 40 °C - +55 °C



Quattro Pin SD

Dimensions (hwxwdx)	85 x 85 x 24 mm
Material	Plastic
Protection class	IP55, pigtail cable, IP54, with connector
Inflammatory class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature	- 40 °C - +55 °C
Storage temperature	- 40 °C - +55 °C



Desktop

Dimensions (hwxwdx)	95 x 62 x 24 mm
Material	Plastic
Protection class	IP67, with the pigtail cable option
Inflammatory class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature	- 40 °C - +55 °C
Storage temperature	- 40 °C - +55 °C



GPRS

Dimensions (hwxwdx)	129 x 193 x 52 mm
Material	Plastic
Protection class	IP67
Operational temperature	-40 °C - +55 °C
Storage temperature	-40 °C - +55 °C



Compact S

Dimensions (hxwx dx)	85 x 85 x 11 mm (with installation frame)
Material	Plastic
Operational temperature	-40 °C - +55 °C
Storage temperature	-40 °C - +55 °C




EPC

Dimensions (hxwx dx)	305 x 305 x 70 mm
Material	Aluminium/Plastic
Protection class	IP67
Operational temperature	-40 °C - +55 °C
Storage temperature	-40 °C - +85 °C



Module and Compact Module

Dimensions (hxwx dx)	Module: 79,5 x 38,5 x 15 mm Compact Module: 39 x 41 x 6 mm
----------------------	---



Woody / Rock

Dimensions (hxwx dx)	Wood: 110 x 43 x 24 mm Rock: ø 120 mm x 20 mm
Material	Wood or Steatite
Protection class	Wood, IP60; Rock, IP67
Operational temperature	Wood: 0° C - +55° C; Rock: -40° C - +55° C
Storage temperature	Wood: 0° C - +55° C; Rock: -40° C - +55° C

