


Low Frequency Tags



CARD
86 x 54 mm



EM 4102 (2402 TAG)
Diameter 24 mm
Thickness 2 mm



LEATHER KEYRING
Optional accessory product
for EM 4102 (2402 Tag)



EM 4102 SAIL
56 x 32 x 8 mm



EM 4102 SAIL
56 x 32 x 8 mm

Low Frequency tag products

- EM 4102 Card
- EM 4102 (2402Tag)
- EM 4102 Sail
- HID Prox Keyfob
- HID Prox Card



EM 4102 Card

Reading distance	Some centimeters
Memory	64 bits
Operating temperature	-20 ... +50 °C
Storage temperature	-20 ... +50 °C
Protection class	IP67
Colour	White

EM 4102 (2402Tag)

Reading distance	Some centimeters
Memory	64 bits
Operating temperature	-25 ... +70 °C
Storage temperature	-25 ... +85 °C
Protection class	IP67
Colour	Red
Other	Accessory black leather keyfob that can be custom-tailored is available for this tag

EM 4102 Sail

Reading distance	Some centimeters
Memory	64 bits
Operating temperature	-40 ... +70 °C
Storage temperature	-40 ... +85 °C
Protection class	IP68
Colour	Black or blue

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi



HID Prox Keyfob

Size	50 x 31 x 10,5 mm
Reading distance	Some centimeters
Operating temperature	-20 ... +70 °C
Storage temperature	-20 ... +70 °C
Protection class	IP66
Colour	Grey
Material	ABS

HID Prox Card

Reading distance	Some centimeters
Operating temperature	-35 ... +70 °C
Storage temperature	-35 ... +70 °C
Protection class	IP68
Colour	White
Material	PVC

Idesco Oy reserves the right to revise this publication and to make changes to its content as well as the right to change or discontinue these products, at any time, without obligation to notify any person or entity of such revisions or changes. All trademarks and registered trademarks are property of their respective owners.
21.11.2024. C00404E v.1.03.

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

