

# ICODE Tag Selection

ICODE SLI Card  
 ICODE 2402 Tag  
 ICODE Sail Tag  
 LOGI TAG 161 ICODE SLI



Idesco offers a wide range of 13.56 MHz tags and cards. Typical applications for these products include access control, time and attendance and asset marking. These products are available as a PVC card, as an epoxy laminated coin tag, and as a polycarbonate Sailtag keyring. All these tag types are suitable for indoor and outdoor use. Both card types have good printability with thermal transfer and thermal sublimation printers.

## Specification

	ICODE SLI CARD	ICODE 2402 Tag	ICODE Sail Tag	LOGI TAG 161 ICODE SLI
<b>Chip Type</b>	ISO 15693 / ISO 18000-3	ISO 15693 / ISO 18000-3	ISO 15693 / ISO 18000-3	ISO 15693 / ISO 18000-3
<b>Size</b>	Credit card 85 x 54 x 1 mm	Diameter 24 mm, Diameter 16 mm, thickness 3 mm	56 x 32 x 8 mm	Diameter 16 mm, thickness 3 mm
<b>Operating Temperature</b>	-20 ... +50 °C	-20 ... +70 °C	-40 ... +70 °C	-20 ... +70 °C
<b>Storage Temperature</b>	-20 ... +50 °C	-25 ... +85 °C	-40 ... +85 °C	-25 ... +85 °C
<b>Protection Class</b>	IP67	IP66	IP68	IP68
<b>Colour</b>	White	White	Black	Grey
<b>Other</b>		Available with a black leather keyfob that can be customer-tailored.		