

ICODE Tag Selection



ICODE SLI CARD
85 x 54 x 1 mm



ICODE 2402 TAG
Diameter 24 / 16 mm
Thickness 3 mm



LEATHER KEYRING
Optional accessory product
for ICODE 2402 Tag



ICODE SAIL TAG
56 x 32 x 8 mm



LOGI TAG 161 ICODE SLI
Diameter 16 mm
Thickness 3 mm

ICODE Tag products

- ICODE SLI CARD
- ICODE 2402 Tag
- ICODE Sail Tag
- LOGI TAG 161 ICODE SLI



ICODE SLI CARD

Chip type	ISO 15693 / ISO 18000-3A
Operating temperature	-20 ... +50 °C
Storage temperature	-20 ... +50 °C
Protection class	IP67
Colour	White

ICODE 2402 Tag

Chip type	ISO 15693 / ISO 18000-3
Operating temperature	-20 ... +70 °C
Storage temperature	-25 ... +85 °C
Protection class	IP66
Colour	White
Other	Accessory black leather keyfob that can be custom-tailored is available for this tag



ICODE Sail Tag

Chip Type	ISO 15693 / ISO 18000-3
Operating Temperature	-40 ... +70 °C
Storage Temperature	-40 ... +85 °C
Protection Class	IP68
Colour	Black

LOGI TAG 161 ICODE SLI

Chip Type	ISO 15693 / ISO 18000-3
Operating Temperature	-20 ... +70 °C
Storage Temperature	-25 ... +85 °C
Protection Class	IP68
Colour	Grey

Idesco Oy reserves the right to revise this publication and to make changes to its content as well as the right to change or discontinue these products, at any time, without obligation to notify any person or entity of such revisions or changes. All trademarks and registered trademarks are property of their respective owners.
17.6.2024. C00405E v.1.03.

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

