



Idesco Reader Housings

Data Sheet

Basic

Robustly reliable, small profile



Specifications

Dimensions (hwxwdx)	110 x 43 x 24 mm
Material	Plastic
IK rating	IK-10
Protection class	Units with cable; IP67. Units with connector; IP54
Flammability class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature range	- 40 °C - +55 °C
Storage temperature range	- 40 °C - +55 °C
Available with Idesco reader technologies	8 CD 2.0, 8 CD 2.0 MI, 8 CD 2.0 OSDPv2, 8 CD 2.0 AES, 8 2.0 CL

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

Slim

Narrow profile suits standard doorframes



Specifications

Dimensions (hwxwdx)	141 x 43 x 19 mm
Material	Plastic
IK rating	IK-09
Protection class	Units with cable; IP67. Units with connector; IP54
Flammability class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature range	- 40 °C - +55 °C
Storage temperature range	- 40 °C - +55 °C
Available with Idesco reader technologies	7 AH, 7 C 2.0, 8 CD 2.0, 8 CD 2.0 MI, 8 CD 2.0 OSDPV2, 8 CD 2.0 AES, 8 2.0 CL, 9 CD 2.0

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

Slim Pin

Pin pad for standard doorframes, for two-factor authentication.



Specifications

Dimensions (hwxwdx)	141 x 43 x 19 mm
Material	Plastic
IK rating	IK-09
Protection class	Units with cable; IP67. Units with connector; IP54
Flammability class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature range	- 40 °C - +55 °C
Storage temperature range	- 40 °C - +55 °C
Available with Idesco reader technologies	7 AH, 7 C 2.0, 8 CD 2.0, 8 CD 2.0 MI, 8 CD 2.0 OSDPV2, 8 CD 2.0 AES, 8 2.0 CL, 9 CD 2.0, 9 CD 2.0 Slim Pin T

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

VS

Visible LED in tough, reliable narrow profile, suitable for standard doorframes



Specifications

Dimensions (h x w x d)	H x W: 148 x 45 mm D: 25,3 mm w/cable 25,3 +10 mm w/connector
Material	Plastic
IK rating	IK-09
Protection class	Units with cable; IP67. Units with connector; IP54
Flammability class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature range	- 30 °C - +55 °C
Storage temperature range	- 30 °C - +55 °C
Available with Idesco reader technologies	8 CD 2.0, 8 CD 2.0 MI, 8 CD 2.0 OSDPv2, 9 CD 2.0

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

VS Pin

Visible LED and reliable pin pad in standard narrow doorframe profile, for two-factor authentication.



Specifications

Dimensions (h x w x d)	H x W: 148 x 45 mm D: 25,3 mm w/cable 25,3 +10 mm w/connector
Material	Plastic
IK rating	IK-09
Protection class	Units with cable; IP67. Units with connector; IP54
Flammability class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature range	- 30 °C - +55 °C
Storage temperature range	- 30 °C - +55 °C
Available with Idesco reader technologies	8 CD 2.0, 8 CD 2.0 MI, 8 CD 2.0 OSDPv2, 9 CD 2.0


Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

VM

Visible LED in tough, reliable housing for
siting over standard electrical sockets



Specifications

Dimensions (hwxwdx)	HxW: 126 x 85 mm D: 28 mm w/cable; 28 +8,5 mm w/connector
Material	Plastic
IK rating	IK-09
Protection class	Units with cable; IP67. Units with connector; IP54
Flammability class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature range	- 30 °C - +55 °C
Storage temperature range	- 30 °C - +55 °C
Available with Idesco reader technologies	8 CD 2.0, 8 CD 2.0 MI, 8 CD 2.0 OSDPv2

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

VM Pin

Visible LED and reliable pin pad for siting over standard electrical sockets, for two-factor authentication.



Specifications

Dimensions (hwxwdx)	HxW: 126 x 85 mm D: 28 mm w/cable; 28 +8,5 mm w/connector
Material	Plastic
IK rating	IK-09
Protection class	Units with cable; IP67. Units with connector; IP54
Flammability class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature range	- 30 °C - +55 °C
Storage temperature range	- 30 °C - +55 °C
Available with Idesco reader technologies	8 CD 2.0, 8 CD 2.0 MI, 8 CD 2.0 OSDPv2, 9 CD 2.0

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

Desktop

Ideal for USB interface or card insertion applications; also supports card coding and enrollment of mobile phone IDs.



Specifications

Dimensions (h x w x d)	95 x 62 x 24 mm
Material	Plastic
Protection class	IP67
Flammability class	Horizontal specimen: UL94 HB Vertical specimen: UL94 V-2
Operational temperature range	- 40 °C - +55 °C
Storage temperature range	- 40 °C - +55 °C
Available with Idesco reader technologies	8 CD 2.0, 8 CD 2.0 MI, 8 CD 2.0 OSDPv2, 9 CD 2.0

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

D Pin

Responsive keypad and function keys, combined with display, to support a wide range of customizable user inputs. For two-factor authentication.



Specifications

Dimensions (h x w x d)	155 x 87 x 20 mm
Material	Plastic
Protection class	IP67
Operational temperature range	- 30 °C - +55 °C
Storage temperature range	- 30 °C - +55 °C
Available with Idesco reader technologies	8CD 2.0 MI OSDPv2


Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

EPC Compact

Visible LED in tough, reliable housing for
siting over standard electrical sockets.



Specifications

Dimensions (h x w x d)	126 x 85 x 36 mm
Material	Plastic
Protection class	IP67
Operational temperature range	- 35 °C - +55 °C
Storage temperature range	- 40 °C - +85 °C
Available with Idesco reader technologies	EPC 2.0 Compact

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

EPC

Built tough, robustly reliable with visible LED, for outdoor, long range applications



Specifications

Dimensions (h x w x d)	305 x 305 x 70 mm
Material	Aluminium/Plastic
Protection class	IP67
Operational temperature range	- 40 °C - +55 °C
Storage temperature range	- 30 °C - +85 °C
Available with Idesco reader technologies	EPC 2.0


Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

Module

PCB module that lets you custom embed
RFID reading into your own device.



Specifications

Dimensions (h x w x d)	79,5 x 38,5 x 15 mm
Available with Idesco reader technologies	7 AH, 7 C 2.0, 8 CD 2.0, 8 CD 2.0 MI, 8 CD 2.0 OSDPv2, 8 CD 2.0 AES


Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi

Compact Module

Compact profile module lets you custom embed in truly small device spaces.



Specifications

Dimensions (hwxwd)	39 x 41 x 6 mm (with connector)
Available with Idesco reader technologies	8 CD 2.0, 8 CD 2.0 MI, 8 CD 2.0 AES

Idesco Oy reserves the right to revise this publication and to make changes to its content as well as the right to change or discontinue these products, at any time, without obligation to notify any person or entity of such revisions or changes. All trademarks and registered trademarks are property of their respective owners.
27.6.2024. C00504E v1.20.

Idesco Oy

Elektroniikkatie 4
90590 Oulu
Finland

Tel. +358 (0)20 743 4175
Email info@idesco.fi
idesco.fi